

CheckEventLog

Check for errors and warnings in the event log.

Queries (Overview)

A list of all available queries (check commands)

- [check_eventlog](#) Check for errors in the event log.

Aliases

A list of all available aliases for queries and check commands

- [CheckEventLog](#) Alternative name for: [check_eventlog](#) Check for errors in the event log.

Commands (executable)

TODO: Add command list

Configuration

Path / Section	Key	Default value	Description
/settings/eventlog/real-time	debug	0	DEBUG
/settings/eventlog/real-time	enabled	0	REAL TIME CHECKING
/settings/eventlog/real-time	log	application,system	LOGS TO CHECK
/settings/eventlog/real-time	startup age	30m	STARTUP AGE
/settings/eventlog/real-time/filters			REALTIME FILTERS
/settings/eventlog	debug	0	DEBUG
/settings/eventlog	lookup names	1	LOOKUP NAMES
/settings/eventlog	buffer size	131072	BUFFER_SIZE
/settings/eventlog	syntax		SYNTAX

Queries (Reference)

A quick reference for all available queries (check commands) in the [CheckEventLog](#) module.

check_eventlog

Check for errors in the event log.

For details on this command go to the [check_eventlog](#) page

Usage: (Click any option to go to the description page for that option)

Option	Description
--------	-------------

	Default value	
<u>help</u>	N/A	Show help screen (this screen)
<u>help-csv</u>	N/A	Show help screen as a comma separated list.
<u>truncate</u>		Truncate the resulting message (mainly useful in older version of nsclient++)
<u>filter</u>		Filter which marks interesting items.
<u>file</u>		The name of an eventlog file the default ones are Application, Security and System. If the specified eventlog was not found due to some idiotic reason windows opens the \application\ " log instead."
<u>syntax</u>		A string to use to represent each matched eventlog entry the following keywords will be replaced with corresponding values: %source%, %generated%, %written%, %type%, %severity%, %strings%, %id% and %message% (%message% requires you to set the description flag) %count% (requires the unique flag) can be used to display a count of the records returned.
<u>date-syntax</u>	%#c	Detail level syntax.
<u>debug</u>	N/A	Enable debug information.
<u>descriptions</u>	N/A	Allow searching and scanning and rendering descriptions field (will be much slower).
<u>unique</u>	N/A	Only return one of each message (based on message id and source).
<u>MaxWarn</u>		Maximum number of matches before a warning is returned.
<u>MaxCrit</u>		Maximum number of matches before a critical is returned.
<u>MinWarn</u>		Minimum number of matches before a warning is returned.
<u>MinCrit</u>		Minimum number of matches before a critical is returned.
<u>warn</u>		Expression which raises a warning status.
<u>crit</u>		Expression which raises a critical status.
<u>ignore-perf-data</u>	N/A	Do not return performance data.
<u>ShowAll</u>	short	Show all values not just problems.
<u>ShowFail</u>		Show all values not just problems.